

DATE	BY	REVISIONS	WAR	BY

SEE REDUCED SCALE
 VIEW OF REAR END

B 128118

RING-RETAINING
 TRUARC #5100-100
 (1) REQD

A 128128

A 128117 (3)

A 127892

B 127853 (2)

C 128119

GEAR-"B" CHANGE #6B508
 16 DP, 50 TEETH, 3.125 P.D.
 (4) REQD

C 128120

BRG.-THRUST OILITE
 #TT-1205-1 (3) REQD

GEAR-BRG. CHANGE #6B29
 16 DP, 29 TEETH-1.813 P.D.
 (2) REQD

BRG. THRUST OILITE
 #TT-1502 (1) REQD

BRG.-FLANGE OILITE
 #FF-1011-2
 (2) REQD

RING RET. TRUARC
 5100-75
 (9) REQD

B 122726

A 122727

WORM - B&W R.H. WORM
 8 P. SINGLE THD. #4L-1076
 (3) REQD

BUSHING-OILITE #FF-1013-4
 (6) REQD (K-092757)

X 061104
 B 018708

188 DRILL AT ASSEMBLY FOR PIN
 AFTER SETTING CROWN PARALLEL TO BED

REDUCED SCALE VIEW
 OF REAR END
 SCALE: .50=1.00

UNLESS OTHERWISE SPECIFIED FINISHED SURFACES HAVE:		DATE	
125 MICRON INCH FINISH	TOLERANCE ±	LITTELL MACH CO 11-26-76	
X AND XX 0.1"	XXX 0.01"	SCALE	1:100 ± 1.00
XXXX 0.001"	X.XXXX 0.0005"	BY	TONKIN
DRINK SHARP CORNERS 0.05 UNLESS OTHERWISE SPECIFIED		TITLE LAYOUT-HEAD ADJUSTMENT	
ORIGINAL ORDER NUMBER 82730-76		REV. 1	
C-128121		C-128121	