


1. TIMKEN 'B'G CONES MAY BE HEATED
IN OIL TO 250° F MAX TO EASE ASSY

2. TIMKEN BEARINGS IN FLYWHEEL TO BE
SHIM ADJUSTED TO ALLOW .005 TO .007
AXIAL MOVEMENT WHILE OPERATING.

F. J. LITTELL MACHINE CO.
CHICAGO, ILLINOIS

LITTELL MACHINE CO. '89-79	
112 MICRONLINE FINISH	112 MICRONLINE FINISH
FINISHES 1	FINISHES 2
X AND EX	6"
X	80°
X	80°
X	80°
BLACK OILY FINISH	BLACK OILY FINISH
83000-77	D 141622
RELEASE	27.500



NOTICE TO PERSON RECEIVING THIS DRAWING: KNOW TECHNICAL INFORMATION.

EXPLANATION: CHANGE PREPARED BY RIGHTS TO THE ORIGINAL DRAWING. THIS DRAWING AND ALL TECHNICAL INFORMATION IS LOANED TO YOU FOR YOUR USE ONLY. IT IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN PERMISSION OF F. J. LITTELL MACHINE CO. THIS DRAWING AND ALL TECHNICAL INFORMATION IS THE PROPERTY OF F. J. LITTELL MACHINE CO. AND IS LOANED TO YOU FOR YOUR USE ONLY. IT IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN PERMISSION OF F. J. LITTELL MACHINE CO.

SEE DETAILS

Airflex

Industrial Clutch Division
Littleton, Colorado

16CR500 CLUTCH FOR
LITTELL BR-4 PRESS
(REF. ESPR 8)

540181 330 LA-7972

105846