



SEE REDUCED SCALE  
 VIEW OF REAR END

B 128118

RING-RETAINING  
 TRUARC #5100-100  
 (1) REQD

A 128128

A 128117

A 127892

B 127853

C 128119

GEAR-BG CHANGE #8508  
 16 DP, 50 TEETH 3.125 PD.  
 (4) REQD

C 128120

BRG.-THRUST OILITE  
 #TT-1205-1 (3) REQD

GEAR-BRG CHANGE #GB29  
 16 DP 29 TEETH-1.813 PD.  
 (2) REQD

BRG.-THRUST OILITE  
 #TT-1502 (1) REQD

BRG.-FLANGE OILITE  
 #FF-1011-2  
 (2) REQD

RING RET. TRUARC  
 5100-75  
 (9) REQD

B 122726

A 122727

WORM-BGW RH. WORM  
 8P SINGLE THD. #4L-1076  
 (3) REQD

BUSHING-OILITE #FF-1013-4  
 (6) REQD (K-092757)

X 061104

B-018708

.188 DRILL AT ASSEMBLY FOR PIN  
 AFTER SETTING CROWN PARALLEL TO BED

REDUCED SCALE VIEW  
 OF REAR END  
 SCALE: .50 = 1.00

UNLESS OTHERWISE SPECIFIED FINISHED SURFACES HAVE: 125 MICROINCH FINISH				DATE 11-26-76 SCALE 1:10 = 1.00 UNIT G. S.
DIMENSIONS	TOLERANCE ±	TITLE LAYOUT-HEAD ADJUSTMENT PART NUMBER LM-1 SHEAR ORIGINAL ORDER NUMBER 82730-76 DWA C 128121 DES		
X AND XX	0.1"			
XXX	0.01"			
XXXX	0.001"			
XXXXX	0.0005"			
BREAK SHARP CORNERS 0.03 UNLESS OTHERWISE SPECIFIED				