
SHEET 2 OF 2 SHEETS
MICROFILMED
FILING LOCATION D-216702
REVISIONS
DATE BY WAS BY
MICROFILMED
SEP 1987
58.000
9.500
SHEAR
.781
K 092439 3 REQ'D
A 128117 3 REQ'D
K 090011 12 REQ'D
K 091983 1 REQ
K 211419 1 REQ
B 211417 1 REQ.
K 090104 B 127856 1 REQ
A 211441 1 REQ
B 211444 1 REQ
K 092439 2 REQ'D
K 211445 2 REQ'D
1 REQ
A 211418
B 127854 1 REQ
A 211416 1 REQ
3.375
WORN
C 211419 1 REQ
A 127892 2 REQ'D
K 092751 6 REQ'D
K 090168 3 REQ'D
K 092750 3 REQ'D (IT)
B 127853 2 REQ'D
C-211420 LAYOUT-GEARTRAIN
GEAR - BG CHANGE GB 25 16 DP, 25 TEETH 1.563 P.D. (3) REQ'D
K 211414
9.500
GEAR - BS CHANGE GB28B 16 DP, 58 TEETH 3.625 P.D. (3) REQ'D
K 211415
K 092440 2 REQ'D
B 127836 2 REQ
(LEFT & RIGHT HAND)
B 216746 1 REQ
3.56
5.25
6.75
4.188
A 225287 2 REQ
B 211448 1 REQ
K 091059 1 REQ
K 211451 2 REQ'D
CROWN #D-211830
UNLESS OTHERWISE SPECIFIED ENDMILL SURFACES SHALL BE 125 MICROINCH FINISH
DIMENSIONS TOLERANCE ±
X AND X.X 0.1"
X.XX 0.01"
X.XXX 0.001"
X.XXXX 0.0005"
ANGLES ± 0° - 30'
BREAK SHARP CORNERS 0.09 UNLESS OTHERWISE SPECIFIED
DRN BY GEE DUCK
DATE 6-13-84
CHK'D BY GEE DUCK
DATE
APP'D BY DLF
DATE 7-2-84
TITLE LAYOUT - CROWN
MATERIAL 8R-5
ORIGINAL ORDER NUMBER 88133-84
SIZE D
DWG. NO. 216702
REV.
SHEET 2
SHEETS 2