D-229670
MICROFILMED
SEP 1987

1. TIMKEN BEARING CUPS CAN BE HEATED IN OIL TO 250°F. MAX. TO EASE ASSEMBLY.
2. TIMKEN BEARINGS IN TYPICAL TO BE SUBJECTED TO ALLOY FOR .000 TO .007 AXIAL TOTAL END OPERATIONS.
3. CLUTCH RATED TORQUE = 25,000 LB.-INCH AT 75% (EXACT TORQUE RATING IS DEPENDENT UPON ACTUAL AIR PRESSURE AND OPERATING SPEED). - BRAKE RATED TORQUE = SEE PARTS LIST
4. EATON WARRANTIES ARE VOID IF THESE SPECIFICATIONS ARE EXCEEDED. - EATON ACCEPTS NO RESPONSIBILITY AND EXTENDS NO WARRANTY IN LIEU OF THOSE APPEARING ANY VARIATION IN ADVANCE.
5. ALL ROTATING EQUIPMENT MUST BE PROTECTED TO COMPLY WITH OSHA STANDARDS.
6. FOR INSTALLATION, OPERATING AND MAINTENANCE, REQUEST FORM: PP-3000
7. WHEN REQUESTING INFORMATION, ALWAYS IDENTIFY THE APPLICATION BY THIS DRAWING NO. AND THE BILL NO. SHOWN, PLUS AIRFLEX FILE NO.

14CB500 ELEMENT ASSY 509656-16 (145211LD)

0000065 x 0045 COTTER PIN (188 Ø x 2.50 LG S.S.)

0000067 x 0015 WASHER (156 THICK)

TO BE PRESS FIT IN REACTION MEMBER

410734-08

"LITTELL" TO SUPPLY

GUARD (BY CUSTOMER)

FLYWHEEL SUB-ASSY 205872 (146105L)

500963 FLYWHEEL

0000001 X 0413 (½-13NC x 2.50 LG HEX HD SCR) 0001100 X 0045 STOP NUT (ESNA 13NE033) 8 REQD., TORQUE TO 38 FT. LBS (DRY)

⅛ QUICK RELEASE VALVE 410584 (135406BK) 2 REQD

404188, 4 REQD

0001146 x 0044 SHIM SET, 2 REQD (TIMKEN: K81505 3 REQD., K21507 3 REQD., K81520 1 REQD)

0001145 X 0002 GREASE FITTING (ALEMITE 1610BC) 0001145 X 0080 RELIEF FITTING (ALEMITE 4120D) 180° (1 PAIR)

0000734 X 0089 (ARP 548-112), 4 REQD

2003471 x 0083 (TIMKEN CONE 43333), 2 REQD 0003446 X 0048 (TIMKEN CUP 43320), 2 REQD

0000001 X 0207 (⅜-16NC x 1.00 LG SCR) 0003739 X 0003 WIRING CLIP (DELCO DL975) 4 REQD. (WIRE IN PAIRS) TORQUE TO 25 FT. LBS (DRY)

DRUM (BY CUSTOMER)

404416-00

0001138 X 0200 (GHRLOCK 53×3536)

CUSTOMER TO LOCATE REACTION PIN TO SUIT PRESS FRAME WITH BRAKE IN PROPER POSITION ON DRUM

VIEW OF BRAKE SCALE: NONE

12CSA200 BRAKE ASSY 511699 (145611DN) "LITTELL" # K-216723

SHAFT (BY CUSTOMER) MIN. RECOMMENDED SHAFT MATL TO BE SAE 4140/4142 ALLOY ROUND HEAT TREATED TO 248-321 BRINELL

203179ND27 SHOWN ON 507376 .875 SQ. x 7.500 LG KEY)

0000001 X 0413 (½-13NC x 2.50 LG SCR) 0000060 X 0013 LOCKWASHER 4 REQD. TORQUE TO 38 FT. LBS. (DRY)

½-14 NPT

0003138 X 0002

0000001 X 0408 (½-13NC x 1.25 LG SCR) 0003736 X 0006 WIRING CLIP (DELCO DL500) 2 REQD. (WIRE TOGETHER)

410745-25

306299

⅛ ROTORSEAL ASSY 202690 (145107AN)

½-13NC x .241 DEEP 2 HOLES @ 180° APART LOCATE AS SHOWN

END VIEW OF SHAFT

E.J. LITTELL MACH. CO. CHICAGO, IL

FOR REF. USED CUSTOMER'S DWG. # 216713

UNLESS OTHERWISE SPECIFIED TOLERANCES SURFACES FINISH					
125 MICROINCH FINISH					
DIMENSION	TOLERANCE				
.X ±.030 X.X	±.010				
.XX	±.005				
.XXX	±.002				
ANGLES ± 30'					
BREAK SHARP, REMOVE BURR UNLESS OTHERWISE SPECIFIED					

DRN		12-14-87	
CHK	SEE DWG		
APP			
LAYOUT - CLUTCH			
MATL			
229670			
SCALE	WEIGHT	SHEET	
62300-150		1 OF 1	

THIRD ANGLE PROJECTION		177227	